

**METHOD FOR ILLUMINATING AN OBJECT WITH LIGHT FROM A
LASER LIGHT SOURCE**

CROSS REFERENCE TO RELATED APPLICATIONS

This invention claims priority of the German patent application 100
5 42 114.8 which is incorporated by reference herein.

FIELD OF THE INVENTION

The present invention relates to a method for illuminating an object
with light from a laser light source, preferably in a confocal scanning microscope.

BACKGROUND OF THE INVENTION

10 Laser light sources are used in a large number of devices and
applications for illuminating objects. In this case, in particular, the advantages of
high coherence length and excellent beam profile, i.e. parallelism of the light
radiation emitted by the laser light source, the outstanding frequency or
wavelength consistency, and the monochromaticity of the light are utilized.

15 The high spatial and temporal coherence of laser light is due to the stimulated
emission by the optical medium in the laser, and has the effect that both the
individual wavelets and the waves emitted at different times interfere virtually
without limitation. The coherence length ℓ of a laser is related to the linewidth $\delta\nu$
by the equation

20
$$\ell = c / (2 \pi \delta\nu)$$

where c is the speed of light. Accordingly, a linewidth $\delta\nu=100$ MHz corresponds
to a coherence length $\ell=0.5$ m. The linewidth, or the coherence length, of a laser

0999726-06290
T 09290 9226660

light source also depends very greatly on the time interval over which the linewidth or the frequency of the laser light source is measured. For example, with large integration times, a laser oscillator exhibits long-term effects which are proportional to the time interval of the measurement and are caused by linear drift
5 of the laser oscillator, for example due to temperature variations.

For some applications, however, a high coherence length is a problem since it can lead to the formation of undesired interference phenomena in the optical beam path. Especially in confocal scanning microscopy, such interference phenomena can induce imaging aberrations.

10

SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide a method with which the coherence length of the laser light can be reduced, so that disruptive interference phenomena can be substantially eliminated. Should interference phenomena nevertheless be formed, these are to be influenced in such
15 a way that they have no effect on the detection.

The method according to the invention of the generic type achieves the above object by the features of Patent Claim 1. According thereto, such a method is characterized in that the phase angle of the light field is varied by a modulation means in such a way that interference phenomena do not occur in the optical beam
20 path, or occur only to an undetectable extent, within a predeterminable time interval.

According to the invention, it has been recognized for the first time that disruptive interference phenomena in the optical beam path can be avoided if the coherence length of the light emitted by the laser light source is less than the optical path in
25 the illumination beam path. Even if disruptive interference phenomena are formed in the optical beam path, a suitable modulation means can be used to vary these

09939726 082801

With the aid of the method according to the invention, it is particularly advantageously possible to use solid-state laser systems, including semiconductor or diode lasers. It is thereby also possible to use narrow-band gas lasers. These laser systems are not so complicated to deal with, and they are less expensive and more compact.

10 Several variants are provided for practical embodiment of the method according to the invention.

In a second variant, a mirror, a lens or a beam splitter is used as the modulation means. This modulation means is also arranged downstream of the laser light source. It is mounted in such a way that it also vibrates or oscillates as a result of vibrations or oscillations of the optical structure or of the casing. In the simplest case, this could involve a lens which is merely placed, but not fixed, in a lens frame. The slight vibrations or oscillations of the device, which are in any case induced, for example, by fans, cause the lens itself to oscillate. The mirror, the lens or the beam splitter could also be moved with the aid of a control element.

The control element could, for example, be a piezo element to which a corresponding control signal is applied.

As a result of the oscillation, vibration and/or movement of the modulation means, the optical path of the light radiation can be stochastically varied, i.e. the length of the optical path is thereby stochastically varied. Owing to the stochastic variation of the optical path, interference phenomena which may occur in the predetermined time interval are also modified, so that an integral detector - a detector which, for example, records the cumulative sum of the light intensity within the predetermined time interval - does not detect the interference phenomenon per se, and accordingly the measurement result is also not disruptively influenced.

In a third variant, provision is made for the modulation means to influence the laser light source. For instance, a modulation means could switch the laser light source on and off. This process of switching on and off would need to take place at least once within the predeterminable time interval. The switching on and off could be performed by corresponding modulation of the pump current of the laser, specifically, for example, if the modulation means periodically interrupts the pump current. More generally, provision could be made for the modulation means to influence the pump current of the laser. In this case, for example, the pump current of a diode laser could be sinusoidally modulated so that the light power emitted by the diode laser is also periodically modified. In this way, it could be possible to vary the wavelength of the light emitted by the diode laser, which should be taken into account in a practical application.

As an alternative to this, provision is made to influence the intensity of the laser light source. This could be done using conventional methods for influencing intensity in laser light sources, for example by Q-switching or cavity dumping.

Furthermore, the modulation means could influence the laser resonator or the optical medium of the laser. In practical terms, provision could be made for the modulation means to be configured as a piezo element which moves and/or

09939726-08801
T.08280-9226660

5

10

15

20

25

The modulation of the phase angle of the light field is synchronized with the scanning process of the confocal scanning microscope. This is useful, in particular, with a view to specifying the time interval, i.e. for example the pixel clock, for successful implementation of the method according to the invention.

- 5 More generally, the modulation of the phase angle of the light field can be synchronized with the object illumination process to be carried out.

- 10 A change in the wavelength of the laser light due to the modulation is advantageously taken into account by the control unit of an AOTF (acousto-optical tunable filter) or AOBS (acousto-optical beam splitter). This component is provided for injecting the laser light into the optical structure, or the confocal scanning microscope. The injection by an AOTF or AOBS is in this case normally adjusted only for a limited wavelength range of the laser light so that, in the event of a change in the wavelength of the laser light due to the modulation, the control unit of the AOTF or AOBS should be changed correspondingly so as not to reduce
15 the injection efficiency.

In a similar way, it would be conceivable for the control unit of an AOTF or AOBS, which injects the laser light, to take into account a change in the power of the laser light due to the modulation. The injection efficiency can again hence be kept substantially constant.

20 **BRIEF DESCRIPTION OF THE DRAWINGS**

- There are, moreover, various possible ways of advantageously configuring and developing the teaching of the present invention. In this regard reference should be made, on the one hand, to the patent claims dependent on Patent Claim 1 and, on the other hand, to the following explanation of the
25 preferred exemplary embodiments of the invention with the aid of the drawing. Generally preferred configurations and developments of the teaching are furthermore explained in connection with the explanation of the preferred

Fig. 1 shows a diagrammatic representation of a confocal scanning microscope in which the method according to the invention is used.

DETAILED DESCRIPTION OF THE INVENTION

According to the invention, the phase angle of the light field is varied by a modulation means 4 designed as an EOM, in such a way that interference phenomena do not occur in the optical beam path, or occur only to an undetectable extent, within a predeterminable time interval.

The EOM 4 is arranged directly downstream of the laser light source 3. A stochastic noise signal 5 is applied to the EOM 4, so that laser light 2 passing through the EOM 4 has a broadened spectral linewidth after its transmission and, accordingly, is injected into the confocal scanning microscope 1 as light 6 with a smaller coherence length. A noise generator 7 is used to produce the noise signal 5.

Via the connection 8, the modulation of the EOM 4 is synchronized with the scanning process of the confocal scanning microscope 1.

20 Lastly, it should more particularly be pointed out that the exemplary embodiments
discussed above are merely used to describe the claimed teaching, but do not
restrict it to the exemplary embodiments.

PARTS LIST

- 1 confocal scanning microscope
- 2 light from (3)
- 3 laser light source
- 4 modulation means, EOM
- 5 noise signal
- 6 the light varied by (4)
- 7 noise generator
- 8 Synchronization connection between (1) and (7)

09939726-082804
"9225660"